


BIADN-IHT Industrial PC



- Onboard Intel® Alder Lake N Processor N97
- Support triple display: LVDS or eDP, 2 x HDMI, USB-C
- Support 1 x DDR4 3200 MHz SO-DIMM, up to 32GB
- Support M.2 Hailo-8™ AI Accelerator, up to 26 TOPS (option)
- 2 x GbE LAN
- 4 x USB3.2 Gen1, 1 x USB-C USB3.2 Gen2 , 6 x USB2.0
- 2 x RS232/422/485, 4 x RS232
- 1x M.2 B key B 3042/3052 support USB3.2+PCIe3.0x1 w/ SIM slot
- 1x M.2 key E 2230 support PCIe3.0x1+USB2.0 for WIFI/BT module
- 1x M.2 M key M 2242/2280 support PCIe3.0x1/ SATA for NVMe/ SATA storage
- DC-IN 9-24V, USB-C PD Sink 20V/5A

Specification

CPU SUPPORT	Intel® Alder Lake-N Processor - Intel® Processor N97
MEMORY	1 x 260-pin DDR4-4800Mhz SO-DIMM, up to 32GB
EXPANSION SLOT	1 x M.2 B key 3042/3052 support PCIe3.0 x1 + USB3.2 w/ SIM slot for 4G/5G module 1 x M.2 M Key 2242/ 2280 support PCIe3.0 x1/ SATA for NVMe/ SATA storage 1 x M.2 E key 2230 support PCIe3.0 x1 +USB2.0 for WIFI/BT module
GRAPHICS	Intel® Integrated Graphics, support triple display - 2 x HDMI1.4 connector (4096x2160@24Hz) - 1 x VGA connector (1920x1200@60Hz) - 1 x LVDS (1920x1200@60Hz) or 1 x eDP (1920*1080@60Hz) - 1 x USB-C connector (4096*2160@60Hz)
AUDIO	Audio Codec: ALC897 + ALC105, support 4 ohm 2W amplifier
LAN	Dual GbE - 2 x Realtek RTL8111H
SUPER I/O CHIP	ITE IT8625E ITE 8764E (support 4COM)
REAR I/O	1 x DC-Jack 2 x HDMI connector 1 x USB-C connector (support DP Alt mode, USB-C PD sink 20V/5A) 2 x USB2.0 Type A connector 2 x USB3.2 Gen1 Type A connector 2 x RJ45 connectors, support 1G

INTERNAL I/O	<p>Expansion slots:</p> <ul style="list-style-type: none"> - 1 x M.2 M key - 1 x M.2 B key w/ SIM Slot - 1 x M.2 E key <p>SATA:</p> <ul style="list-style-type: none"> - 1 x SATA3 7pin connector - 1 x 1*4 pin SATA power box header <p>Display:</p> <ul style="list-style-type: none"> - 1 x 2*20 pin LVDS box header - 1 x 1*40 pin eDP box header (opt) - 1 x 1*8 pin LCD backlight control box header (5V/12V) - 1 x 2*3 pin LCD power select header (3.3V/5V/12V, default is 3.3V) <p>Audio:</p> <ul style="list-style-type: none"> - 1 x 2*5 pin box header for MIC-in, Line-out, Line-in - 1 x 1*4 pin box header for 4 ohm 2W amplifier speaker <p>USB:</p> <ul style="list-style-type: none"> - 2 x 2*5 pin header, support 4 x USB2.0 - 1 x 2*10 pin box header, support 2 x USB3.2 Gen1 <p>Power:</p> <ul style="list-style-type: none"> - 1 x 2*2 ATX connector , support DC-IN 9~24V <p>Serial Port:</p> <ul style="list-style-type: none"> - 2 x 2*5 pin RS232/422/485 box header (COM5/COM6) - 2 x 2*5 pin RS232 box header (COM1/COM2/COM3/COM4) - 6 x 2*3 pin COM power select header (RI/5V/12V, default is RI) <p>Others:</p> <ul style="list-style-type: none"> - 1 x buzzer - 1 x 2*5 8-bit DIO pin header - 1 x 1*4 pin CPU Fan header - 1 x 1*3 pin system Fan header - 1 x 1*2 pin clear CMOS header - 1 x 2*3 pin DIO power select header (1.8V/3.3V/5V, default is 3.3V) - 1 x 2*7 front panel header - 1 x 1*5 pin SMBus box header - 1 x 1*4 pin I2C box header - TPM2.0 onboard
DIMENSION	Thin Mini-ITX, 170 mm x 170 mm x 1.6mm (W x L)
ENVIRONMENT	0°C ~ 60°C Humidity : 5% ~ 90%
OS SUPPORT	Support Windows 10 IoT Enterprise 21H2/ Winddows 11 IoT Enterprise 24H2 Support Ubuntu 22.04

*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!