

# BIW88-AHS Industrial PC



**COMING SOON**

## Specification

CPU SUPPORT	LGA1851, support Intel® Core Ultra 200 Processor
CHIPSET	Intel W880
MEMORY	4 x 288-pin DDR5-6400Mhz U-DIMM(ECC/ Non-ECC), up to 196GB
EXPANSION SLOT	2 x M.2 M Key 2242/2280 support PCIe5.0 x4 /PCIe4.0 x4 for NVMe storage 1 x M.2 E Key 2230 support PCIe4.0 x1 + USB2.0, support WIFI/BT module 2 x PCIe5.0 x16 (x16+NA or x8+x8) 4 x PCIe4.0 x4 Slot (1xPCIe4.0 x4 share with M.2 M Key) 1 x PCIe4.0 x1
GRAPHICS	Intel® Integrated Graphics, support triple display - 1 x HDMI 2.0 connectors (4096x2160@60Hz) - 1 x DP++1.4 connector (4096x2160 @60Hz) - 1 x VGA connector (1920x1200 @60Hz)
AUDIO	Audio Codec: ALC897
LAN	Quad Intel® LAN 3 x 2.5G by I226-V 1 x 2.5G by I226-LM, support Intel vPro
SUPER I/O CHIP	IT8786E-I
REAR I/O	1 x COM Port , support RS-232/422/485 1 x VGA connector 1 x DP connector 1 x HDMI connector 4 x RJ45 connector, support 2.5G 8 x USB3.2 Gen2 Type A connector 3 x Audio jacks, support Line-in/Line-out/Mic-in

INTERNAL I/O	<p>Expansion slots: Expansion slots:</p> <ul style="list-style-type: none"> <li>- 4 x 288-pin DDR5 sockets</li> <li>- 1 x M.2 key M type, support PCIe5.0 x4 SSD</li> <li>- 1 x M.2 key M type, support PCIe4.0 x4 SSD( share w/ PCIe4.0 x4)</li> <li>- 2 x PCIe5.0 x16 (x16+NA or x8+x8)</li> <li>- 4 x PCIe4.0 x4 Slot (1xPCIe4.0 x4 share with M.2 M key</li> <li>- 1 x PCIe4.0 x1</li> </ul> <p>SATA:</p> <ul style="list-style-type: none"> <li>- 6 x SATA3 7pin connector</li> </ul> <p>Audio:</p> <ul style="list-style-type: none"> <li>- 1 x 2*5 pin header for MIC-in, Line-out</li> </ul> <p>USB:</p> <ul style="list-style-type: none"> <li>- 2 x USB2.0 by 1 x 2*5 pin header</li> <li>- 1 x USB2.0 Type A</li> <li>- 2 x USB3.2 Gen1 by 1x 2*10 pin header</li> </ul> <p>Power:</p> <ul style="list-style-type: none"> <li>- 1 x 2*4 pin CPU power connector</li> <li>- 1 x 2*12 pin ATX power connector</li> </ul> <p>Serial Port:</p> <ul style="list-style-type: none"> <li>- 1 x 2*5 pin RS232/422/485 box header</li> <li>- 4 x 2*5 pin RS232 box header</li> <li>- 6 x 2*3 pin COM power select header (RI/5V/12V, default is RI)</li> </ul> <p>Others:</p> <ul style="list-style-type: none"> <li>- 1 x 2*13 Parallel port pin-header (Multi-function with DIO)</li> <li>- 1 x 1*3 DIO voltage select header (5V/3.3V, default 3.3V)</li> <li>- 1 x 2*2 DIO/Printer function select header</li> <li>- 1 x 1*5pin SMBus header</li> <li>- 1 x 1*4pin-header for CPU Fan (PWM Fan)</li> <li>- 3 x 1*4pin-header for SYS Fan (PWM Fan)</li> <li>- 1 x 2*5 pin front panel header</li> <li>- 1 x 1*3 pin clear CMOS header</li> <li>- 1 x 1*3 pin AT/ATX mode select header (default is ATX)</li> <li>- TPM2.0 onboard</li> </ul>
DIMENSION	ATX 305 x 244 x1.6mm ( W x L )
ENVIRONMENT	0°C ~ 60°C Humidity : 5% ~ 90%
OS SUPPORT	Support Windows 11 24H2 Support Ubuntu 24.04

\*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!