

BIOS User Guide

B450GT3

BIOS Update	2
UEFI BIOS Setup	6
SMART FAN Control	7
VIVID LED Control	8
1. Main Menu	9
2. Advanced Menu	10
3. Chipset Menu.....	24
4. Boot Menu.....	28
5. Security Menu.....	30
6. O.N.E Menu.....	32
7. Exit Menu.....	35

BIOS Update

The BIOS can be updated using either of the following utilities:

- **BIOSTAR BIOS-FLASHER:** Using this utility, the BIOS can be updated from a file on a hard disk, a USB drive (a flash drive or a USB hard drive), or a CD-ROM.
- **BIOSTAR BIOS Update Utility:** It enables automated updating while in the Windows environment. Using this utility, the BIOS can be updated from a file on a hard disk, a USB drive (a flash drive or a USB hard drive), or a CD-ROM, or from the file location on the Web.

BIOSTAR BIOS-FLASHER


Note

- » This utility only allows storage device with FAT32/16 format and single partition.
- » Shutting down or resetting the system while updating the BIOS will lead to system boot failure.


Updating BIOS with BIORSTAR BIOS-FLASHER

1. Go to the website to download the latest BIOS file for the motherboard.
2. Then, copy and save the BIOS file into a USB flash (pen) drive.(Only supported FAT/FAT32 format)
3. Insert the USB pen drive that contains the BIOS file to the USB port.
4. Power on or reset the computer and then press <F12> during the POST process.


5. After entering the POST screen, the BIOS-FLASHER utility pops out. Choose <fs0> to search for the BIOS file.



6. Select the proper BIOS file, and a message asking if you are sure to flash the BIOS file. Click "Yes" to start updating BIOS.



7. A dialog pops out after BIOS flash is completed, asking you to restart the system. Press the <Y> key to restart system.



8. While the system boots up and the full screen logo shows up, press key to enter BIOS setup.

After entering the BIOS setup, please go to the <Save & Exit>, using the <Restore Defaults> function to load Optimized Defaults, and select <Save Changes and Reset> to restart the computer. Then the BIOS Update is completed.


BIOS Update Utility (through the Internet)

1. Installing BIOS Update Utility from the DVD Driver.
2. Please make sure the system is connected to the internet before using this function.


3. Launch BIOS Update Utility and click the “Online Update” button on the main screen.




4. An open dialog will show up to request your agreement to start the BIOS update. Click “Yes” to start the online update procedure.




5. If there is a new BIOS version, the utility will ask you to download it. Click “Yes” to proceed.



6. After the download is completed, you will be asked to program (update) the BIOS or not. Click “Yes” to proceed.



7. After the updating process is finished, you will be asked you to reboot the system. Click “OK” to reboot.



8. While the system boots up and the full screen logo shows up, press key to enter BIOS setup.


After entering the BIOS setup, please go to the <Save & Exit>, using the <Restore Defaults> function to load Optimized Defaults, and select <Save Changes> and <Reset> to restart the computer. Then, the BIOS Update is completed.

BIOS Update Utility (through a BIOS file)


1. Installing BIOS Update Utility from the DVD Driver.
2. Download the proper BIOS from <http://www.biostar.com.tw/>



3. Launch BIOS Update Utility and click the “Update BIOS” button on the main screen.




4. A warning message will show up to request your agreement to start the BIOS update. Click “OK” to start the update procedure.




5. Choose the location for your BIOS file in the system. Please select the proper BIOS file, and then click on “Open”. It will take several minutes, please be patient.

6. After the BIOS Update process is finished, click on “OK” to reboot the system.



7. While the system boots up and the full screen logo shows up, press key to enter BIOS setup.

After entering the BIOS setup, please go to the <Save & Exit>, using the <Restore Defaults> function to load Optimized Defaults, and select <Save Changes and Reset> to restart the computer. Then, the BIOS Update is completed.



Backup BIOS

Click the Backup BIOS button on the main screen for the backup of BIOS, and select a proper location for your backup BIOS file in the system, and click “Save”.

UEFI BIOS Setup

Introduction

The purpose of this manual is to describe the settings in the AMI UEFI BIOS Setup program on this motherboard. The Setup program allows users to modify the basic system configuration and save these settings to NVRAM.

UEFI BIOS determines what a computer can do without accessing programs from a disk. This system controls most of the input and output devices such as keyboard, mouse, serial ports and disk drives. BIOS activates at the first stage of the booting process, loading and executing the operating system. Some additional features, such as virus and password protection or chipset fine-tuning options are also included in UEFI BIOS.

The rest of this manual will to guide you through the options and settings in UEFI BIOS Setup.

Plug and Play Support

This AMI UEFI BIOS supports the Plug and Play Version 1.0A specification.

EPA Green PC Support

This AMI UEFI BIOS supports Version 1.03 of the EPA Green PC specification.

ACPI Support

AMI ACPI UEFI BIOS support Version 1.0/2.0 of Advanced Configuration and Power interface specification (ACPI). It provides ASL code for power management and device configuration capabilities as defined in the ACPI specification, developed by Microsoft, Intel and Toshiba.

PCI Bus Support

This AMI UEFI BIOS also supports Version 2.3 of the Intel PCI (Peripheral Component Interconnect) local bus specification.

Using Setup

When starting up the computer, press **** during the **Power-On Self-Test (POST)** to enter the UEFI BIOS setup utility.


In the UEFI BIOS setup utility, you will see **General Help** description at the top right corner, and this is providing a brief description of the selected item. **Navigation Keys** for that particular menu are at the bottom right corner, and you can use these keys to select item and change the settings.

► Note

- » *The default UEFI BIOS settings apply for most conditions to ensure optimum performance of the motherboard. If the system becomes unstable after changing any settings, please load the default settings to ensure system's compatibility and stability. Use Load Setup Default under the Exit Menu.*
 - » *For better system performance, the UEFI BIOS firmware is being continuously updated. The UEFI BIOS information described in this manual is for your reference only. The actual UEFI BIOS information and settings on board may be slightly different from this manual.*
 - » *The content of this manual is subject to be changed without notice. We will not be responsible for any mistakes found in this user's manual and any system damage that may be caused by wrong-settings.*
-

SMART FAN Control

Press <F5> to display the SMART FAN Control menu.



- 1. CPU1/2 RPM & SYSTEM1/2/3 RPM:** Click button to set the status value of CPU and system fan.
- 2. PWM/Temperature Panel:** According to the fan PWM value corresponding to CPU and system temperature to adjust the fan speed.
 » Allows you to adjust according to your preferences.
- 3. Temperature:** Shows the current CPU and system temperature.
- 4. Control Mode:** Allows you to control mode of the fans.
 - **Quiet:** Enable Quiet mode.
 - **Aggressive:** Enable Aggressive mode.
 - **Manual:** Enable Manual mode.
 - **Full on:** Enable Full On mode.
- 5. User Selection:** Sets the fan property controls the actual selection operation.
 - **Auto:** Allows you to adjust the Automatic detection Mode.
 - **DC:** Allows you to adjust the Direct Current (DC) Mode.
 - **PWM:** Allows you to adjust the Pulse Width Modulation (PWM) Mode.

Note

- » Menu contents will be different slightly, depending on different motherboard of users' computers.
- » Once you are finished making your selections, choose the <Save & Exit> menu to save.

VIVID LED Control

Press <F6> to display the VIVID LED Control menu.



1. LED SPARKLE: Allows to you choose sparkle of the LEDs.

- **Permanent:** LEDs are constantly lit.
- **Breath:** LEDs gradually flash on and off.
- **Shine:** LEDs flash at a specific frequency.
- **OFF:** Allows you to enable or disable VIVID LED of a single item.

2. LED COLOR:

- **Auto:** LEDs will Automatically change the Color Palette and LED Brightness.

» If you select Auto mode, the Color Pallette and LED Brightness Bar will disabled.

- **Default:** All the setting are back to default.

3. LED Type: Select the LED lighting blocks.

- **RGB Header 1:** The header 1 LED illumination. (RGB LED Device)
 - **RGB Header 2:** The header 2 LED illumination. (RGB LED Device)
 - **RGB Audio:** The RGB Audio LED illumination. (On board LED or VIVID LED ARMOR)
- » This item will no support LED COLOR function.

• **System:** System LED illuminations. (MOSFET Heatsink LED, Southbridge Heatsink LED)

4. ON/OFF: To enable or disable VIVID LED function.

5. Color Palette: Allows to you choose specific color of the LEDs.

6. LED Brightness Bar: Allows you to adjust the LED brightness.


▶ Note

» Menu contents will be different slightly, depending on different motherboard of users' computers.

» Once you are finished making your selections, choose the <Save & Exit> menu to save.

1. Main Menu

Once you enter AMI UEFI BIOS Setup Utility, the Main Menu will appear on the screen providing an overview of the basic system information.



2. Advanced Menu

The Advanced Menu allows you to configure the settings of CPU, Super I/O, Power Management, and other system devices.

Note

» Beware of that setting inappropriate values in items of this menu may cause system to malfunction.



Note

» The AMD CBS option appears only with Summit Ridge/ Raven Ridge/ Pinnacle Ridge.

Trusted Computing



Security Device Support

This item enables or disables BIOS support for security device. O.S. will not show Security Device.
TCG EFI protocol and INT1A interface will not be available.

Options: Enabled (Default) / Disabled

SHA-1 PCR Bank

This item enables or disables SHA-1 PCR Bank.

Options: Enabled (Default) / Disabled

SHA256 PCR Bank

This item enables or disables SHA256 PCR Bank.

Options: Enabled (Default) / Disabled

Pending operation

This item Schedule an Operation for the Security Device.

Options: None (Default) / TPM Clear

» *Your computer will reboot during restart in order to change state of Security Device.*

Platform Hierarchy

This item enables or disables Platform Hierarchy.

Options: Enabled (Default) / Disabled

Storage Hierarchy

This item enables or disables Storage Hierarchy.

Options: Enabled (Default) / Disabled

Endorsement Hierarchy

This item enables or disables Endorsement Hierarchy.

Options: Enabled (Default) / Disabled

TPM2.0 UEFI Spec Version

This item select the TCG2 Spec Version support. TCG_1_2: the Compatible mode for Win8/Win10 ; TCG_2: Support new TCG2 protocol and event format for Win10 or later.

Options: TCG_2 (Default) / TCG_1_2


Physical Presence Spec Version

This item select to tell O.S. to support PPI Spec Version 1.2 or 1.3 .

Options: 1.3 (Default) / 1.2

» *Note some HCK tests might not support 1.3 .*

ACPI Settings / WakeUp Event control



PS2 Keyboard PowerOn

This item allows you to control the keyboard power on function.

Options: Disabled (Default) / Any Key / Stroke Key / Specific Key

Stroke Keys

This item will show only when Keyboard PowerOn is set "Stroke Key."

Options: Wake Key (Default) / Power Key / Ctrl+F1 / Ctrl+F2 / Ctrl+F3 / Ctrl +F4 / Ctrl+F5 / Ctrl+F6

Specific Key


This item will show only when Keyboard PowerOn is set "Specific Key." Press Enter to set Specific key.

PS2 Mouse PowerOn

This item allows you to control the mouse power on function.

Options: Disabled (Default) / Enabled

SATA Configuration



OnChip SATA function

This item enables or disables OnChip SATA function.


Options: Enabled (Default) / Disabled

OnChip SATA Type


This item select OnChip SATA Type.

Options: AHCI (Default) / RAID

Promontory Common Options




PT USB Configuration Options




PT XHCI GEN1/2

Options: Auto (Default) / Disabled / Enabled

IT8625 Super IO Configuration



Serial Port 1 Configuration



Serial Port

This item enables or disables Serial Port.

Options: Enabled (Default) / Disabled

Change Settings

This item select an optimal settings for Super IO Device.

Options: Auto (Default) / IO=3F8h; IRQ=4 / IO=3F8h; IRQ=3,4,5,6,7,9,10,11,12 / IO=2F8h;

IRQ=3,4,5,6,7,9,10,11,12 / IO=3E8h; IRQ=3,4,5,6,7,9,10,11,12 /

IO=2E8h; IRQ=3,4,5,6,7,9,10,11,12

H/W Monitor



PWM Processor Hot

Options: Enabled (Default) / Disabled


Shutdown Temperature

This item allows you to set up the CPU shutdown Temperature.

Options: Disabled (Default) / 70°C/158°F / 75°C/167°F / 80°C/176°F / 85°C/185°F / 90°C/194°F

CPU Configuration

This item shows CPU Information.



PowerNow

This item enables or disables the generation of ACPI _PPC, _PSS, and _PCT objects.

Options: Enabled (Default) / Disabled

NX Mode

This item enables or disables No-execute page protection Function.

Options: Enabled (Default) / Disabled

SVM Mode

This item enables or disables CPU Virtualization.

Options: Enabled (Default) / Disabled

CPB Mode

This item specifies the method of core performance boost enablement.

Options: Enabled (Default) / Disabled

C6 Mode

This item enables or disables C6.

Options: Auto (Default) / Enabled / Disabled

PCI Subsystem Settings**PCI Latency Timer**

This item value to be programmed into PCI Latency Timer Register.

Options: 32 PCI Bus Clocks (Default) / 64 PCI Bus Clocks / 96 PCI Bus Clocks / 128 PCI Bus Clocks / 160 PCI Bus Clocks / 192 PCI Bus Clocks / 224 PCI Bus Clocks / 248 PCI Bus Clocks

PCI-X Latency Timer

This item value to be programmed into PCI Latency Timer Register.

Options: 64 PCI Bus Clocks (Default) / 32 PCI Bus Clocks / 96 PCI Bus Clocks / 128 PCI Bus Clocks / 160 PCI Bus Clocks / 192 PCI Bus Clocks / 224 PCI Bus Clocks / 248 PCI Bus Clocks

VGA Palette Snoop

This item enables or disables VGA Palette Registers Snooping.

Options: Disabled (Default) / Enabled

Above 4G Decoding

This item enables or disables 64bit capable Devices to be Decoded in Above 4G Address Space
(Only if System Supports 64bit PCI Decoding).

Options: Disabled (Default) / Enabled

SR-IOV Support

This item if system has SR-IOV capable PCIe Devices, this option enables or disables Single Root IO Virtualization Support.


Options: Disabled (Default) / Enabled

BME DMA Mitigation

This item Re-enable Bus Master Attribute disabled during PCI enumeration for PCI Bridges after SMM Locked.

Options: Disabled (Default) / Enabled

PCI Express Settings



No Snoop

This item enables or disables PCI Express Device No Snoop option.

Options: Enabled (Default) / Disabled

Maximum Payload

This item set Maximum Payload of PCI Express Device or allow System BIOS to select the value.

Options: Auto (Default) / 128 Bytes / 256 Bytes / 512 Bytes / 1024 Bytes / 2048 Bytes / 4096 Bytes

Maximum Read Request

This item set Maximum Read Request Size of PCI Express Device or allow system BIOS to select the value.


Options: Auto (Default) / 128 Bytes / 256 Bytes / 512 Bytes / 1024 Bytes / 2048 Bytes / 4096 Bytes

ASPM Support


This item set the ASPM Level: Force L0s - Force all links to L0s State ; AUTO - BIOS auto configure ; Disable - Disable ASPM.

Options: Disabled (Default) / Auto / Force L0s

USB Configuration



Network Stack Configuration



Network Stack

This item enables or disables UEFI network stack

Options: Disabled (Default) / Enabled

Note

» The following items appear only when you set the Network Stack function to [Enabled]

IPv4 PXE Support

This item enables or disables IPv4 PXE Boot Support. If disabled IPv4 PXE boot option will not be created.

Options: Disabled (Default) / Enabled

IPv4 HTTP Support

This item enables or disables IPv4 HTTP Boot Support. If disabled IPv4 HTTP boot support will not be created.

Options: Disabled (Default) / Enabled

IPv6 PXE Support

This item enables or disables IPv6 PXE Boot Support. If disabled IPv6 PXE boot option will not be created.

Options: Disabled (Default) / Enabled

IPv6 HTTP Support

This item enables or disables IPv6 HTTP Boot Support. If disabled IPv6 HTTP boot support will not be available.

Options: Disabled (Default) / Enabled

IPSec Certificate

This item enables or disables IPSec Certificate for IKE.

Options: Enabled (Default) / Disabled


PXE boot wait time

Wait time to press ESC key to abort the PXE boot.

Media detect count

Number of times presence of media will be checked.

CSM Configuration



CSM Support

This option enables or disables CSM support.

Options: Enabled (Default) / Disabled

GateA20 Active

Upon Request – GA20 can be disabled using BIOS services. Always – do not allow disabling GA20; this option is useful when any RT code is executed above 1MB.

Options: Upon Request (Default) / Always

Option ROM Messages

This item set display mode for Option ROM.

Options: Force BIOS (Default) / Keep Current

INT19 Trap Response

This item BIOS reaction on INT19 trapping by Option ROM: IMMEDIATE - execute the trap right away ; POSTPONED - execute the trap during legacy boot.

Options: Postponed (Default) / Immediate

HDD Connection Order

This some OS require HDD handles to be adjusted, i.e. OS is installed on drive 80h.

Options: Adjust (Default) / Keep

Boot option filter

This option controls Legacy/UEFI ROMs priority.

Options: UEFI and Legacy (Default) / Legacy only / UEFI only

Network

This option controls the execution of UEFI and Legacy Network OpROM

Options: Legacy (Default) / UEFI / Do not launch

Storage

This option controls the execution of UEFI and Legacy Storage OpROM
Options: Legacy (Default) / UEFI / Do not launch

Video

This option controls the execution of UEFI and Legacy Video OpROM
Options: Legacy (Default) / UEFI / Do not launch


Other PCI device ROM priority

This item for PCI devices other than Network, Mass storage or Video defines which OpROM to launch.


Options: UEFI (Default) / Legacy / Do not launch

NVMe Configuration

The item shows NVMe controller and driver information.



Offboard PCIe SATA Controller




3. Chipset Menu


This section describes configuring the PCI bus system. PCI, or Personal Computer Interconnect, is a system which allows I/O devices to operate at speeds nearing the speed of the CPU itself uses when communicating with its own special components.

Note


» Beware of that setting inappropriate values in items of this menu may cause system to malfunction.



South Bridge



SB USB Configuration



XHCI Controller

This item enables or disables XHCI Controller.


Options: Auto (Default) / Enabled / Disabled

EHCI HC(Bus 0 Dev 18 Fn 0)

This item enables or disables EHCI Controller.

Options: Auto (Default) / Disabled / Enabled

North Bridge




IOMMU

This item enables or disables IOMMU support.

Options: Disabled (Default) / Enabled

GFX Configuration



Primary Video Device (Bristol Ridge/ Raven Ridge Only)

This item select Primary Video Device that BIOS will use to for output.

Options: NB PCIe slot Video (Default) / IGD Video

Integrated Graphics (Bristol Ridge/ Raven Ridge Only)

This item allows you to controller the Integrated Graphics function.

Options: Auto (Default) / Disabled

UMA Frame Buffer Size (Bristol Ridge/ Raven Ridge Only)

This item allows you to set UMA FB Size.

Options: Auto (Default) / 32M / 64M / 128M / 256M / 512M / 1G / 2G

Gnb Hd Audio

This item enable or disable Gnb Hd Audio Support.

Options: Auto (Default) / Enabled / Disabled

PSPP Policy

This item allows you to set PCIe speed power policy.


Options: Auto (Default) / Disabled / Performance / Balanced-High / Balanced-Low / Power Saving

Surround View (Bristol Ridge/ Raven Ridge Only)

This item support multi-display function.

Options: Disabled (Default) / Auto

Onboard Device



Realtek PCIE NIC

This item enables or disables Realtek PCIE NIC.

Options: Enabled (Default) / Disabled


Onboard LAN Option ROM

This item enables or disables Onboard LAN Option ROM.

Options: Disabled (Default) / Enabled

4. Boot Menu

This menu allows you to setup the system boot options.



Setup Prompt Timeout

This item sets number of seconds to wait for setup activation key.

Options: 2 (Default)

Bootup NumLock State

This item selects the keyboard NumLock state.

Options: On (Default) / Off

Full Screen Logo Display

This item enable or disable Full Screen Logo Show function.

Options: Enabled (Default) / Disabled

Fast Boot

This item enable or disable boot with initialization of a minimal set of devices required to launch active boot option. Has no effect for BBS boot options.

Options: Disabled (Default) / Enabled

Note

» The following items appear only when you set the Fast Boot function to [Enabled]

SATA Support

If Last Boot HDD Only, Only last boot HDD device will be available in Post. If All Sata Devices, all SATA devices will be available in OS and Post.

Options: Last Boot HDD Only (Default) / All Sata Devices

VGA Support

If Auto, only install Legacy OpRom with Legacy OS and logo would NOT be shown during post.
EFI driver will still be installed with EFI OS.

Options: EFI Driver (Default) / Auto

USB Support

If Disabled, all USB devices will NOT be available until after OS boot. If Partial Initial, USB Mass Storage and specific USB port/device will NOT be available before OS boot. If Enabled, all USB devices will be available in OS and Post.

Options: Full Initial (Default) / Disabled / Partial Initial

PS2 Devices Support

If Disabled, PS2 devices will be skipped.

Options: Enabled (Default) / Disabled

Network Stack Driver Support

If Disabled, Network Stack Drivers will be skipped.

Options: Disabled (Default) / Enabled

Redirection Support

If Disabled, Redirection function will be disabled.

Options: Disabled (Default) / Enabled

BIOS Flash protection

While enabled, it can't flash write and flash erase by SMI.

Options: Enabled (Default) / Disabled

Boot Success Beep

This item BIOS boot post beep message.

Options: Enabled (Default) / Disabled

5. Security Menu




Administrator Password

This item sets Administrator Password.

User Password

This item sets User Password.

Secure Boot Menu



Secure Boot

Secure Boot flow control. Secure Boot can be enabled only when 1. Platform Key (PK) is enrolled and Platform is operating in user mode and 2.CSM function is disabled in Setup.

Options: Disabled (Default) / Enabled

» Note: The following items appear only when you set the Secure Boot function to [Enabled]

Key Management



Restore Factory keys

Force System to User Mode. Configure NVRAM to contain OEM-defined factory default Secure Boot Keys.

Reset To Setup Mode

This item delete NVRAM content of all UEFI Secure Boot Key databases.

Platform Key (PK)

Options: Details / Export / Update / Delete

Key Exchange Keys

Options: Details / Export / Update / Append / Delete

Authorized Signatures

Options: Details / Export / Update / Append / Delete

Forbidden Signatures

Options: Details / Export / Update / Append / Delete

Authorized Timestamps

Options: Update / Append

OsRecovery Signatures


Options: Update / Append

6. O.N.E Menu

This submenu allows you to change voltage and clock of various devices.

Note

- » We suggest you use the default setting. Changing the voltage and clock improperly may damage the device.
- » The options and default settings might be different by RAM or CPU models.
- » Beware of that setting inappropriate values in items of this menu may cause system to malfunction.
 - Values in Red: Danger
 - Values in Yellow: Warning
 - Values in White: Normal



CPU Ratio

This item allows you to set the CPU Ratio

Options: Auto (Default)

Memory Clock Mode

This item select the DRAM Frequency programming method. If Auto, the DRAM speed will be based on SPDs. If Manual, the DRAM speed specified will be programmed regardless of SPD.

Options: Auto (Default) / Manual

Note

- » The following items appear only when you set the Memory Clock Mode function to [Manual]

Memory Frequency

This item select the memory clock value in MHz.

Options: Auto (Default) / DDR4 1333 / DDR4 1600 / DDR4 1866 / DDR4 2133 / DDR4 2400

DDR Memory Voltage

This item allows you to control DDR Memory Voltage.

Options: Auto (Default)

CPU Core Voltage

This item allows you to control CPU Core Voltage.

Options: Auto (Default)

CPU_SOC Voltage

This item allows you to control CPU_SOC Voltage Control.

Options: Auto (Default)

VDDP Voltage

This item allows you to control VDDP.


Options: Auto (Default)

DDR VPP Voltage

This item allows you to control DDR VPP Voltage.


Options: Auto (Default)

Memory Insight



DIMM Profile

These items display memory information.



RACING+

FS : Fan F6 : Vivid Led

CPU
3 100 MHZ 1.372 +

DRAM
2 400 MHZ 1.222 +

TEMP
3 42

2018 Jul 13

00:00

Main Advanced Chipset Boot Security **O.N.E.** Save & Exit

DIMM1 Profile

Capacity N/A


Frequency Standard

tCL tRCD tRAS tCWL tRFW tREFI tRFC tRTP tMR tRDO_S tRRD_L tKTR_S tHTR_L NMode Voltage

•+: Select Screen
↑/↓Click: Select Item
Enter/Dbl Click: Select
+/−: Change Opt.
F1: General Help
F3: Optimized Defaults
F4: Save & Exit
ESC/RIGHT Click: Exit
F11: BIOS Screen Capture
F12: BIOS Flash

7. Exit Menu

This menu allows you to load the optimal default settings, and save or discard the changes to the BIOS items.



Discard Changes and Exit

Abandon all changes made during the current session and exit setup.

Save Changes and Reset

Reset the system after saving the changes.

Restore Defaults

Restore/Load Default values for all the setup options.

Launch Shell from device

This item attempts to EFI Shell application (Shell.efi) from one of the available filesystem devices.

Saving SetupData to Profile

This item Saving SetupData to Profile.

Options: 1

Restoring SetupData from Profile

This item Restoring SetupData from Profile.

Options: 1

Saving SetupData to Storage

This item saves your current BIOS Setup Data to storage devices.

Restoring SetupData from Storage

This item restores your BIOS Setup Data from storage devices.